

ISH-12G

12G-SDI TO HDMI 2.0 CONVERTER



Front View



Rear View

Product Summary

The ISH-12G is a high-performance video signal converter that reliably converts 12G-SDI input signals into 4K HDMI output. It is designed to easily integrate 12G-SDI signals used in professional broadcast and video equipment with a wide range of displays and video devices that support HDMI interfaces, offering excellent versatility and compatibility across diverse AV and broadcast environments.

Key Features

- Integrated support for 3G, 6G, 12G-SDI
- Video Input : YCbCr 4:2:2 8bit
- Audio: Supports 48kHz or 96kHz, up to 16 channels
- Video Output : YCbCr 4:2:2, YCbCr 4:2:0

Specifications

Item	Specification
Model	ISH-12G
Input	12G-SDI 1 Port
Output	HDMI 1 Port [HDMI Type A Connector] / 12G-SDI 1 Port
Video Input	YCbCr 4:2:2 8bit
Video Output	YCbCr 4:2:2, YCbCr 4:2:0
Power	DC + 5V / 3A
Dimensions (WxHxD)	100 x 28.25 x 87(mm)
Weight	0.5kg
Operating Temperature	0°C ~ 40°C
Operating Humidity	Up to 80% RH (Non-Condensing)

※ Notes

Rev. 1 | 20260806
* Specifications and design are subject to change without prior notice.